


Exoplanets with the James Webb Space Telescope John Mather, NASA's GSFC January 10, 2009



JWST Mission "At a Glance"




Organization

- Mission Lead: Goddard Space Flight Center
- International collaboration with ESA & CSA
- Prime Contractor: Northrop Grumman Space Technology
- Instruments:
 - -Near Infrared Camera (NIRCam) Univ. of Arizona
 - -Near Infrared Spectrograph (NIRSpec) ESA
 - -Mid-Infrared Instrument (MIRI) JPL/ESA
 - -Fine Guidance Sensor (FGS) CSA
- Operations: Space Telescope Science Institute

Description

- Deployable infrared telescope with 6.5 meter diameter segmented adjustable primary mirror
- Cryogenic temperature telescope and instruments for infrared performance
- Launch 2013 on an ESA-supplied Ariane5 rocket to Sun-Earth L2
- 5-year science mission (10-year goal)



JWST Science Themes




End of the dark ages: First light and reionization



The assembly of galaxies



Birth of stars and proto-planetary systems



Planetary systems and the origin of life




JWST Science Working Group (#4)

- 6 Interdisciplinary Scientists: H. Hammel, S. Lilly, J. Lunine, M. McCaughrean, M. Stiavelli, R. Windhorst
- Instrument Team Lead/ Science Representative: M. Rieke (NIRCam), G. Rieke and G. Wright (MIRI), Rene Doyon (FGS), & rotating scientist member, NIRSpec
- Telescope Scientist: M. Mountain (also STScI Director)
- Ex Officio: J. Mather (Chair), J. Gardner, M. Clampin, M. Greenhouse, K. Flanagan, G. Sonneborn, P. Jakobsen, J. Hutchings




Project Summary Document

 Gardner et al. 2006, Space Science Reviews, 123/4, 485 http:// jwst.gsfc.nasa.gov/ scientists.html






Three Mirror Anastigmat Optical Design Provides a Wide Field-of-View




JWST Instruments










Four science instruments enable imagery and spectroscopy over the 0.6 – 29 micron spectrum










Field Position of Science Instruments

Boundary of Unvignetted field



Instruments and Guidance Sensor Share Telescope Field of View



Sensitivity & Resolution

- Cameras and R \sim 100 spectroscopy background limited at all wavelengths
 - 6.5 m mirror much larger than HST, Spitzer big gains
 - Background dominated by zodi light, and at > 12 μ m from thermal emission from sunshield
 - Other stray light from galaxy, sometimes Earth or Moon
- NIRSpec sensitivity detector limited at $R \sim 1000$
- Image quality
 - Diffraction limited ($\lambda/14$ rms wavefront) at 2 μ m (\sim ground AO)
 - 0.034 arcsec pixels in NIRCam short band (Nyquist @ 2 μ m)
 - 0.068 arcsec in NIRCam long band and Fine Guider
 - 0.2 x 0.45 arcsec shutters for NIRSpec
 - 0.11 arcsec pixels for MIRI camera
 - 0.19 0.28 arcsec pixels for MIRI image slicer integral field unit



TABLE IX
Science instrument characteristics

Instrument	Wavelength(µm)	Plate scale Detector (milliarcsec/pixel) Field of view				
NIRCam	9000-9000 0000 5 00 - 9 9000 7 0 0000 6		32	2.2 × 4.4 arcmin		
Short	0.6-2.3	Eight				
		2048×2048				
Long ^a	2.4-5.0	Two	65	2.2×4.4 arcmin		
	2048×2048					
NIRSpec	0.6-5.0	Two	100			
MSA^b			2048×2048	3.4×3.1 arcmin		
Slits ^c				\sim 0.2 \times 4 arcsec		
IFU				$3.0 \times 3.0 arcsec$		
MIRI	5.0-29.0	1024×1024	110			
Imaging				1.4×1.9 arcmin		
Coronagraphy				$26 \times 26 arcsec$		
Spectrad	5.0-10.0			$0.2 \times 5 arcsec$		
IFU	5.0-29.0	Two	200 to 470	3.6×3.6		
		1024×1024		to 7.5×7.5 arcsec		
TFI	1.6-4.9e	2048×2048	65	2.2×2.2 arcmin		

^bNIRSpec includes a microshutter assembly (MSA) with four 365×171 microshutter arrays. The individual shutters are each 203 (spectral) \times 463 (spatial) milliarcsec clear aperture on a 267×528 milliarcsec pitch.



JWST Sensitivities

TABLE X
Instrument sensitivities

Instrument/mode	$\lambda (\mu \mathrm{m})$	Bandwidth	Sensitivity
NIRCam	2.0	R = 4	11.4 nJy, AB = 28.8
TFI	3.5	R = 100	126 nJy, AB = 26.1
NIRSpec/Low Res.	3.0	R = 100	132 nJy, AB = 26.1
NIRspec/Med. Res.	2.0	R = 1000	$1.64 \times 10^{-18} \mathrm{erg s^{-1} cm^{-2}}$
MIRI/Broadband	10.0	R = 5	700 nJy, AB = 24.3
MIRI/Broadband	21.0	R = 4.2	$8.7 \mu\text{Jy}, AB = 21.6$
MIRI/Spect.	9.2	R = 2400	$1.0 \times 10^{-17} \mathrm{erg s^{-1} cm^{-2}}$
MIRI/Spect.	22.5	R = 1200	$5.6 \times 10^{-17} \mathrm{erg s^{-1} cm^{-2}}$

Note. Sensitivity is defined to be the brightness of a point source detected at 10σ in $10,000\,\mathrm{s}$. Longer or shorter exposures are expected to scale approximately as the square root of the exposure time. Targets at the North Ecliptic Pole are assumed. The sensitivities in this table represent the best estimate at the time of submission and are subject to change.

Observing the "First" Light

TABLE II JWST measurements for the end of the dark ages theme

Observation	Instrument	Depth, Mode	Target
Ultra-deep survey (UDS)	NIRCam	$1.4\mathrm{nJy}$ at $2\mu\mathrm{m}$	10 arcmin ²
In-depth study	NIRSpec	23 nJy, $R \sim 100$	Galaxies in UDS area
	MIRI	23 nJy at 5.6 μ m	Galaxies in UDS area
Lyman α forest diagnostics	NIRSpec	$2 \times 10^{-19} \mathrm{erg} \mathrm{cm}^{-2} \mathrm{s}^{-1},$ $R \sim 1000$	Bright $z > 7$ quasar or galaxy
Survey for Lyman α sources	TFI	$2 \times 10^{-19} \mathrm{erg}\mathrm{cm}^{-2}\mathrm{s}^{-1},$ $R \sim 100$	4 arcmin ² containing known high-z object
Transition in Lyman α/Balmer	NIRSpec	$2 \times 10^{-19} \mathrm{erg} \mathrm{cm}^{-2} \mathrm{s}^{-1},$ $R \sim 1000$	UDS or wider survey area
Measure ionizing continuum	NIRSpec	2×10^{-19} erg cm $^{-2}$ s ⁻¹ , $R \sim 1000$	Same data as above
Ionization source nature	NIRSpec	$2 \times 10^{-19} \mathrm{erg} \mathrm{cm}^{-2} \mathrm{s}^{-1},$ $R \sim 1000$	Same data as above
	MIRI	23 nJy at 5.6 μ m	
LF of dwarf galaxies	NIRCam	$1.4\mathrm{nJy}$ at $2\mu\mathrm{m}$	UDS data



Assembly of Galaxies

TABLE III

JWST measurements for the assembly of galaxies theme


Observation	Instrument	Depth, Mode	Target
Deep-wide survey (DWS)	NIRCam	3 nJy at 3.5 μm	100 arcmin ²
Metallicity determination	NIRSpec	$5 \times 10^{-19} \text{ erg s}^{-1} \text{cm}^{-2}$, $R \sim 1000$	Galaxies in DWS
Scaling relations	MIRI	11 μ Jy at 9 μ m, $R \sim 3000$	Lyman Break galaxies at $z \sim 3$
	NIRCam	3 nJy at 3.5 μ m	DWS data
Obscured galaxies	MIRI	23 nJy at $5.6 \mu m$	ULIRGs
	NIRSpec	$5 \times 10^{-19} \text{ erg s}^{-1} \text{ cm}^{-2}$, $R \sim 1000$	ULIRGs and AGN
	MIRI	$1.4 \times 10^{-16} \mathrm{erg \ s^{-1} cm^{-2}}$ at $24 \mu\mathrm{m}$, $R \sim 2000$	ULIRGs and AGN

January 10, 2009 Mather JWST JPL 13



A NIRCam Imaging Module












NIRSpec Schematic





January 10, 2009 Mather JWST JPL 15



NIRSpec: ESA & Astrium


- > 100 Objects Simultaneously
- 9 square arcminute FOV





• Implementation:


- 3.5' Large FOV Imaging Spectrograph
- 4 x 175 x 384 element Micro-Shutter Array
- 2 x 2k x 2k Detector Array
- Fixed slits and IFU for backup, contrast
- SiC optical bench & optics



Mid-Infrared Instrument (MIRI)



- Science team G. Rieke (lead), G.Wright (co-lead)
- European Consortium sponsored by ESA in partnership with NASA/JPL
- Science Goals include
 - Search for the origins of galaxies
 - Birth of stars and planets
 - Evolution of planetary systems
- Imaging
 - λ =5-29 μm wavelength range
 - Diffraction limited imaging with 0.1" pixels
 - ~1.7' field of view
 - Able to image sources as bright as 4 mJy at λ=10μm
 - ≥12 bandpass filters
 - Low resolution spectrograph (R~100; λ=5-10 μm) for single, compact sources
 - Simple coronagraph
- Spectroscopy
 - λ =5-29 μm wavelength range, reach λ = 28.3 μm
 - Integral field spectroscopy with > 3" field of view
 - R~2000-3700 from λ =5-29 μm




Optics Module concept developed by European Consortium



Fine Guidance Sensor (FGS)





- Guide star availability with >95% probability at any point in the sky Wide open bandpass for guiding (0.5 μm 5.0 μm)
- Includes Tunable Filter Imager with R = 70 150, 1.7 μ m 4.8 μ m Coronagraph

2008 Progress



General

- JWST successfully completed Non-Advocate Review and Confirmation Review and is approved to begin Implementation Phase
- All observatory components, except for the spacecraft and membrane management system of the sunshield, have successfully completed their preliminary design reviews
- All science instruments successfully completed critical design reviews
- HQ approved moving object tracking requirement
- Telescope and Mirrors
 - All flight primary, secondary and tertiary mirrors completed machining and are in stages of rough polishing, smooth out and figure grinding
 - Mirror "Manufacturing Percentage" progressed from 41% to 55%
- Observatory
 - Sunshield Preliminary Design Review held in February 2008
 - Observatory Integration & Test control room opened at NGST
- Ground Segment
 - Delivered all Science Instrument Integrated Test Sets (SITSs) and Science Instrument Development Units (SIDUs) to SI teams in the US, Canada and Europe

2008 Progress continued



Integrated Science Instrument Module (ISIM)

MIRI

- MIRI Verification Model (VM) completed, tested and achieved 6.2K operating temperature and first light!
- Selected flight detectors for MIRI

NIRSpec

- Delivered Engineering Test Unit detector subsystem to Astrium
- Selection of flight detectors agreed to by NASA & ESA
- ESA approved larger (1.6 arcsec square) aperture for NIRSpec for transits

NIRCam

- Selected ALL flight detectors and filters for NIRCam
- Completed bonding and vibration testing of the NIRCam ETU Optical Bench

- FGS

- Held FGS System CDR at COM DEV
- Engineering Test Unit assembly begun, tunable filter etalon tested at cryo
- CSA added Non-Redundant Masking to their Tunable Filter Imager

Structure


Completed bonding 5 of 13 Flight Hardware Decks

Primary Mirror Segment Assembly Flight Hardware Production Well Underway







Launch Restraint Flexures



Flight actuators under test





PM Bipod Mounting Brackets




Strongback Struts


PM Whiffle Assemblies

PM Delta Frames 1-8

Installation of Test Stand with Mass Simulators into MSFC XRCF Test Chamber Complete











Al and EDU at the XRCF





January 10, 2009

Mather JWST JPL




Flight Backplane Started





JSC Chamber A Modification Progress











External chamber modifications – removal of solar simulator structures

ETU Hardware Queuing Up for Instrument I&T





NIRSpec Focal Plane Assembly



NIRCam Shortwave Camera Triplet & Beamsplitter



NIRCam Pupil Imaging Lens Mechanism




NIRSpec Fore Optics

2009 Major Events



- Sunshield Membrane Management System Preliminary Design Review, February
- ISIM Critical Design Review, March
- Assembly & Testing of NIRCam Engineering Test Unit, June
- Observatory Flight Software Build | Critical Design, June
- Microshutter device delivered from GSFC to NIRSpec, June
- NIRCam Flight Instrument build commences, August
- Electro-optical tests of ETU FGS at operating conditions, October
- Mission Critical Design Review scheduled for December
- MIRI Flight Instrument testing commences



2007 Tucson conference proceedings out soon

JWST Project seeking Associate Project Scientist for Integration and Test See AAS job bulletin position 25420

The James Webb Space Telescope Capabilities for Astrobiology

Mark Clampin
JWST Observatory Project Scientist
Goddard Space Flight Center



contributors: Jonathan Lunine, George Rieke, Don Lindler (GSFC), Eliza Miller-Ricci (CfA), Sara Seager (MIT), Tom Greene (NASA/Ames), Drake Deming (GSFC), and JWST SWG and SI Teams



The NASA Astrobiology Roadmap

 Goal I — Understand the nature and distribution of habitable environments in the universe. Determine the potential for habitable planets beyond the Solar System, and characterize those that are observable.

• GOAL 7 — Determine how to recognize signatures of life on other worlds and on early Earth. Identify biosignatures that can reveal and characterize past or present life in ancient samples from Earth, extraterrestrial samples measured in situ or returned to Earth, and remotely measured planetary atmospheres and surfaces. Identify biosignatures of distant technologies.



Documentation

- Astrobiology Whitepaper: Lunine & Seager
 - (Google "jwst white paper")
- JWST Coronography Whitepaper

JWST Transit Science Whitepaper

Space Science Reviews



Astrobiology Themes

- High contrast imaging and spectroscopy of Brown Dwarfs and Extrasolar Giant Planets
- Formation of planetary systems: tracing evolution of planetary systems from dust clouds to debris disks
- Studies of water and prebiotic organics in comets;
- Characterize organic and inorganic matter needed to create habitable environments
- Characterization of exoplanets via transit imaging

Transit Science Instrument Modes



SI	λ (μm)	Spectral Resolution (λ/δλ)	FOV	Mode	Comments	Application
NIRCam	0.6 - 2.3 2.4 - 5.0	4, 10, 100 4, 10, 100	2 x (2.2' x 2.2') 2 x (2.2' x 2.2')	Imaging Imaging	Photometric Imaging	High precision light curves of transits from photometry of point source images. Wavelength coverage permits photometric monitoring of primary or secondary eclipses.
NIRCam	0.6 – 2.3	4, 10, 100	2 x (2.2' x 2.2')	Phase diversity imaging	Defocusing of images to 57 or 114 pixel diameters	High precision light curves of transits associated with bright objects which need to be defocused to avoid saturation within the minimum integration time
NIRCam	2.4 – 5.0	2000	2 x (2.2' x 2.2')	Long-λ Grism	Backup capability for WFSC. Used with F277W, F322W, F356W, F410M or F444W	Emission spectroscopy of hot gas giant transiting planets
NIRSpec	1.0 – 5.0	100, 1000, 2700	0.1" x 2.0", 0.2" x 3.5", 0.4"x 4.0"	Spectroscopy	Fixed long slits	Low and intermediate resolution transmission and emission spectroscopy of transiting planets.
NIRSpec	0.7 - 5.0	2700	3" x 3"	Spectroscopy	Integral Field Unit	Intermediate resolution, transmission and emission spectroscopy of transiting planets.
MIRI	5 – 29	4-6	1.9' x 1.4'	Imaging	Photometric Imaging	
MIRI	5 - 11	100	5" x 0.2"	Spectroscopy	Fixed Slit or Slitless	Light curves of transits from photometry of point source images.
MIRI	5.9 – 7.7 7.4 – 11.8 11.4 – 18.2 17.5 – 28.8	3000 3000 3000 3000	3.7" x 3.7" 4.7" x 4.5" 6.2"x 6.1" 7.1"x7.7"	Spectroscopy	Integral field unit	Intermediate resolution, emission spectroscopy of transiting planets.
TFI	1.6 – 2.5	100	2.2' x 2.2'	Imaging	Selectable central λ	High precision light curves of transits from photometry of point source images. Wavelength coverage permits photometric monitoring of primary eclipses.
TFI	3.2 – 4.9	100	2.2' x 2.2'	Imaging	Selectable central λ	High precision light curves of transits from photometry of point source images. Wavelength coverage permits photometric monitoring of secondary eclipses.

JWST.


NIRCam Team Transit Science

- R~1700 over entire LW channel, λ = 3 5 μ m simultaneously (but limited by filters in series)
- No slit losses w/good sampling (0.065" vs NIRSpec 0.1")
 - Precise transit spectrophotometry
 - Especially important for eclipse mapping
- Defocused imaging for transit photometry
 - Sub-arrays available for defocused imaging
 - 4λ, 8λ, 12λ waves of defocus












NIRCam Performance

- Secondary eclipses of a hot Jupiter around bright
 G2V stars realistic to detect in R≤500 spectra.
- Hot Earths cannot be detected around G2V stars in R=500 secondary eclipse spectra

- High S/N R=500 spectra of a Jupiter around M2-3V stars can be observed via secondary eclipse.
- Secondary transits of Hot Earths around M5V stars could be detected at low SNR in R~50 spectra in ~10⁴ sec

NIRCam IIII MIRI





CH4, CO, H2O constrain temperature and C abundance

Red symbols are measurements;

Top curve has fluz absorbed on day side only; bottom has uniform energy redistribution

Dashed line is BB

Charbonneau, Knutson, Barman, Allen, Mayor, Megeath, Queloz, & Udry (2008)

October 2008

Exoplanet Transits with JWST



MIRI Team Science


Imager can observe bright sources with good sampling


 MIRI imager should detect even small (1-2 R_⊕) planets when transiting bright GKM stars

- LRS may be best to characterize the spectra of hot giant planets with high S/N and at R<=100 spectral resolution
 - Hot giant features detectable in a single transit @ R~50!
- MRS will be useful for R = 100 2000 spectra
 - 3 settings required to cover any broad spectral range



NIRSpec Team Science






NIRSpec Transit Spectrum for HD 209458 at K=12

- NIRSpec designed for multi-object
- Recently added 1.6'x1.6" slit for transit spectroscopy
- Undersampled pixels remain a concern wrt systematics



Model Spectra


 The Atmospheric Signatures of Super-Earths: How to Distinguish Between Hydrogen-Rich and Hydrogen-Poor Atmospheres, Eliza Miller-Ricci, Sara Seager & Dimitar Sasselov, 2008arXiv0808.1902M





GL 581 - Hrich Superearth


- NIRSpec 20 transits
- Binned to R~300






GJ436 _ Transmission


- NIRSpec 4 transits
- Binned to R~300






NAMES A. ESA. CER


Crop of Recent Detections!



Fomalhaut B Kalas et al. 2008



HR 8799 Marois et al. 2008



β Pictoris A. M. lagrange et al. 2009



Imaging/Spectroscopy Modes

Instrument	Channel/Mode	λ (μ m)	R (λ/δλ)
NIRCam	Short λ Lyot Coronagraph	0.6 - 2.3	4, 10, 100
NIRCam	Long λ Lyot Corongagraph	2.4 - 5.0	4, 10, 100
TFI	Multi-λ coronagraph	1.6 - 2.5	100
TFI	Multi-λ coronagraph	3.2 - 4.9	100
TFI	Non-redundant mask	1.6 - 2.5	100
TFI	Non-redundant mask	3.2 - 4.9	100
MIRI	Quadrant Phase Coronagraph	10.65	20
MIRI	Quadrant Phase Coronagraph	11.4	20
MIRI	Quadrant Phase Coronagraph	15.5	20
MIRI	Lyot Coronagraph	23	5

High Contrast Imaging

MIRI	Integral field spectrograph	5.86 - 7.74	3000
MIRI	Integral field spectrograph	7.43 - 11.84	3000
MIRI	Integral field spectrograph	11.44 - 18.20	3000
MIRI	Integral field spectrograph	17.53 - 28.75	2250
NIRSpec	Integral field spectrograph	0.7 - 5.0	2700

Integral Field Spectroscopy




Coronography (Dressler summary)

- NIRCam coronagraph (Krist 2007; Greene et al 2006)
 - Inner Working angle $\geq 4\lambda/D$ (500-750 mas at 3-5 μ m)
 - Outer Working Angle ±10"
 - Dynamic range 10⁵ (12.5mag) 10⁶ (15 mag) far from star
- TFI/Non Redundant Mask (Sivaramakrishnan et al)
- Inner Working angle ~ $0.5\lambda/D$ (75 mas at 5 μ m)
- Outer Working Angle 0.5"
- Dynamic range 10^4 (10 mag) possibly up to 10^6 (12.5 mag) with careful calibration, flat fielding
 - MIRI classic Lyot and 4-quadrant phase plate
- Mostly disks but also planets on distant orbits (Fomalhaut-b)




NIRCam: M0V Star at 4 pc (F460M)





Exoplanet Imaging Discovery Space



Courtesy M. Meyer

JWST.

Tunable Filter Imager Coronagraph

- TFI Coronagraphic Capability Summary
 - Wavelength range:

1.5-2.5, 3.1-5.0


μm


- Field of view: 20"x20"
- Coronagraph: Differential Speckle Imaging
- **Contrast** gain of ~10x versus NIRCam
- Inner working angle: $4 \text{ } \text{$\lambda$}/D$
- Technique employed on HR8799 (Marois et al. 2008)
- Non-redundant Mask
 - Wavelength range:

1.5-2.5, 3.1-5.0

μm

- Coronagraph: Closure Phase Imaging
- Trades inner working angle: 0.5 λ/D against contrast






200 150 100 50 Sivaramakrishnan et al 2009 50 100 150 200

Non-Redundant Mask Imaging

- New mode for FGS/TFI utilizes "interferometric" mask producing 21 baselines and a narrow PSF (0.5λ/D)
- Ground-based contrast limits ~5 mag, in space > 10 mag possible at small IWA
- Flat fielding issues may be problem (>>Photon noise) for bright stars



Performance of the Non-redundant phase mask



Table $1 - Log_{10}$ of planet/star contrast at 4.6 μ m (TFI Coronagraph)¹

Table 1 20010 or Printer state to the printer to the Cart State Branch													
		0.01 Gyrs			0.10 Gyrs		1 Gyrs		5 Gyrs				
Sp	M_m	1	5	10	1	5	10	1	5	10	1	5	10
		M_J	$M_{\rm J}$	M_J	M_J	$M_{\rm J}$	$M_{\rm J}$	M_J	$M_{\rm J}$	$M_{\rm J}$	$M_{\rm J}$	$M_{\rm J}$	M_J
A0	0.78	-5.09	-4.16	-3.78	-5.96	-4.94	-4.47	-7.67	-5.83	-5.33	-8.87	-6.95	-5.97
F0	2.27	-4.49	-3.56	-3.18	-5.37	-4.35	-3.88	-7.07	-5.24	-4.74	-8.27	-6.36	-5.38
G2	3.58	-3.97	-3.04	-2.66	-4.84	-3.82	-3.35	-6.55	-4.71	-4.21	-7.75	-5.83	-4.85
K 0	4.29	-3.68	-2.76	-2.38	-4.56	-3.54	-3.07	-6.26	-4.43	-3.93	-7.46	-5.55	-4.59
K 5	4.69	-3.52	-2.60	-2.22	-4.40	-3.38	-2.91	-6.10	-4.27	-3.77	-7.30	-5.39	-4.41
M0	5.15	-3.34	-2.41	-2.03	-4.22	-3.20	-2.72	-5.92	-4.08	-3.58	-7.12	-5.20	-4.22
M5	7.98	-2.21	-1.28	-0.9	-3.08	-2.06	-1.59	-4.79	-2.95	-2.45	-5.99	-4.07	-3.09
L0	10.15	-1.34	-0.41	-0.03	-2.22	-1.20	-0.72	-3.92	-2.08	-1.58	-5.12	-3.22	-2.22
L5	10.98	-1.01	-0.08	0.30	-1.88	-0.86	-0.39	-3.59	-1.75	-1.25	-4.79	-2.88	-1.89
T0	11.40	-0.84	0.09	0.48	-1.72	-0.70	-0.22	-3.42	-1.58	-1.08	-4.62	-2.70	-1.72
T5	12.38	-0.45	0.48	0.86	-1.33	-0.31	0.16	-3.03	-1.20	-0.70	-4.23	-2.31	-1.34

Contrast exceeds the 10 σ sensitivity beyond 1". 2

Contrast exceeds the 10 σ sensitivity beyond 5". 2

Contrast exceeds the 10σ sensitivity beyond 1" without coronagraph and no PSF calibration.


¹ Evolutionary models from Barraffe et al 2003.

² Contrast threshold assuming the 2" (FWHM) occulting spot and a speckle noise attenuation factor ~10x




MIRI Exoplanet Detection Limits


Boccaletti et al.



M2V, 10pc




Detection limit (5-σ) with 30-m groundbased telescope




Signal to noise ratio of EGPs at 11μm as a function of the radial separation assuming a system located at 10 pc around an M2V star. The dotted and solid lines correspond respectively to the signal to noise ratio in the first and the second filters (ammonia absorption)




Debris Disks: HST's Legacy




HD 107146 Ardila et al. 2005




HD 15115 Kalas et al. 2005



HD 92945 Clampin et al. 2006



HR 4796 Schneider et al. 1999



HD 207129 Stapelfeldt et al. 2007



HD 139644 Kalas et al. 2006




HD 51543 Kalas et al. 2006




HD 181327 Schneider et al. 2006



HD 141569A Weinberger et al. 1999




HD 10647 Stapelfeldt et al. 2007




HD 32297 Schneider et al. 2006 Krist et al. 2005




AU Mic



Fomalhaut Kalas et al. 2005



β Pictoris Golimowski et al. 2005





HD 202917 Clampin et al. 2007


A-ESA-CO

Debris Disks: Evidence for Planets


Warps










Spirals



Brightness Asymmetries










Offsets







Clumps















MIRI: Disk Characterization

• Disk morphology: scattered light & emission







Summary

- JWST is on track for 2013 launch a major accomplishment!
- Predicted performance for exoplanet transits is very good (limited by systematic errors and unknown stability)
- 3 coronagraphs provided but segmented aperture not optimal
- Small changes made for better photometric stability (NIRSpec) and better inner working angle (TFI non-redundant mask)



The End

January 10, 2009 Mather JWST JPL 54


JWST NEST

Pluto?






Debris Disks: β Pictoris






JWST Observations of Fomalhaut





Direct Detection





- Mark McCaughrean, a JWST SWG member and astrophysicist at the University of Exeter quoted by BBC
- "It's like a London bus you've been waiting for one for ages and suddenly four come along at once."



and more to come!



Flight Mirror AI



